

# 3MP+3MP HD Indoor Dual-lens PT Wi-Fi Camera

## Uho-S3S-M33D



### Key Features



- Fixed camera and PT camera integration, dual channels with one IP, look at overall situation and consider details at the same time
- Ultra 265, H.265, H.264
- Support digital WDR (Wide Dynamic Range)
- Built-in Mic & Speaker, support two-way audio, offer better interaction
- Support sound and light warning, makes warning and alarming more noticeable
- Smart IR, up to 10m (33ft) IR and 10m (33ft) warm light distance, suitable for more scenes
- IR & warm light illumination to deal with different scenes and achieve full-color illumination
- Supports 512 GB Micro SD card
- Wi-Fi connection and easy installation


## Specifications

Uho-S3S-M33D					
Camera	Panorama			Detail	
Sensor	1/2.8" progressive scan, 3.0 megapixel, CMOS			1/2.8" progressive scan, 3.0 megapixel, CMOS	
Min. Illumination	Colour:0.01 lux (F2.0,AGC ON) 0 lux with IR			Colour:0.01 lux (F2.0,AGC ON) 0 lux with IR	
Day/Night	IR-cut filter with auto switch (ICR)			IR-cut filter with auto switch (ICR)	
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000s				
WDR	DWDR				
S/N	>52dB				
Lens					
Lens type	4.0mm@F2.0			4.0mm@F2.0	
Digital Zoom	N/A			4X	
Iris	Fixed			Fixed	
Field of View (H)	91.5°			91.5°	
Field of View (V)	48.1°			48.1°	
Field of View (D)	96.3°			96.3°	
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0 mm	73.5 (241.0ft)	29.4 (96.4ft)	14.7 (48.2ft)	7.3(24.1ft)
	4.0 mm	73.5 (241.0ft)	29.4 (96.4ft)	14.7 (48.2ft)	7.3(24.1ft)
Illuminator					
IR Range	Up to 10m (33ft)			Up to 10m (33ft)	
Warm Light Range	N/A			Up to 10m (33ft)	
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264				
Frame Rate	Main Stream: 3MP (2304*1296), Max 15fps; 2MP (1920*1080), Max 15fps; 720P (1280*720), Max 15fps; Sub Stream: 640*360,Max 15fps; 2CIF(704*288), Max 15fps; CIF(352*288), Max 15fps;			Main Stream: 3MP (2304*1296), Max 15fps; 2MP (1920*1080), Max 15fps; 720P (1280*720), Max 15fps; Sub Stream: 640*360,Max 15fps; 2CIF(704*288), Max 15fps; CIF(352*288), Max 15fps;	
Video Bit Rate	128 Kbps~2048 Kbps				
ROI	Up to 8 areas				
Video Stream	Dual streams				
OSD	Up to 4 OSDs				
Privacy Mask	Support(Only NVR)				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°				
HLC	N/A				
BLC	N/A				

Defog	Digital Defog	
<b>Events</b>		
Basic Detection	Motion detection, Ultra motion detection(pedestrian/motor vehicle/pet), Loud Sound Detection, Crying detection, Tampering alarm	
Auto tracking	N/A	Support
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication	
<b>Audio</b>		
Audio Compression	G.711U,G.711A	
Audio Bitrate	64 Kbps	
Two-way Audio	Support	
Suppression	Support	
Sampling Rate	8 kHz	
<b>Storage</b>		
Edge Storage	Micro SD, up to 512 GB	
Network Storage	ANR	
<b>Network</b>		
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n/ax), built-in antenna	
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP	
Compatible Integration	API	
Client	Uniarch Client Uniarch APP	
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above	
<b>Wi-Fi</b>		
Wireless Standards	IEEE802.11b/g/n/ax	
Frequency Range	2.4 GHz ~ 2.4835 GHz	
Channel Bandwidth	20/40 MHz Support	
Modulation Mode	802.11b: CCK 802.11g/n: OFDM 802.11ax: OFDMA	
Security	64/128-bit WEP, WPA-PSK/WPA2-PSK	
Transmit Power	802.11b: 17±1.5dBm @11Mbps 802.11g: 16±1.5dBm @ 54Mbps 802.11n: 16±1.5dBm @MCS7 802.11ax: 16±1.5dBm @MCS9	
Receive Sensitivity	802.11b: -76dBm @11Mbps (Typical) 802.11g: -65dBm @54Mbps (Typical) 802.11n: -61dBm @MCS7,HT40(Typical) 802.11ax: -54dBm @MCS9,HE40(Typical)	
Transmission Rate	802.11b: 11Mbps 802.11g: 54Mbps 802.11n: up to 150Mbps 802.11ax: up to 270Mbps	
<b>Pan &amp; Tilt</b>		
Pan Range	N/A	0° ~ 355°
Pan Speed	N/A	17°/s ~ 50°/s
	Preset speed: N/A	Preset speed: 50°/s

Tilt Range	0° ~ 15°	-15° ~ 90°
Tilt Speed	N/A	17°/s ~ 50°/s
	Preset speed: N/A	Preset speed: 50°/s
Number of Presets	20	
<b>Interface</b>		
Built-in Mic	Support	
Built-in Speaker	Support	
Wi-Fi	Support	
Network	1 * RJ45 10M/100M Base-TX Ethernet	
<b>Certifications</b>		
EMC	CE EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)	
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)	
Safety	CE LVD (EN 62368-1)	
Environment	CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU)	
<b>General</b>		
Power	DC 5V/1.5A	
	USB type-C interface	
Dimensions (Ø x H)	Φ80 x 127mm (Ø3.1" x 4.8")	
Weight	0.22kg(0.49lb)	
Working Environment	-10°C~50°C(-14°F ~ 122°F), Humidity: ≤95% RH (non-condensing)	
Storage Environment	-10°C~50°C(-14°F ~ 122°F), Humidity: ≤95% RH (non-condensing)	
Surge Protection	N/A	
Reset Button	Support	
LED indicator	1, red/blue	

## Dimensions



[www.uniview.com/uniarch](http://www.uniview.com/uniarch)

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.